

## WP-S01 Series 20W-50W IP66 Wall Mount Speaker



### Features:

- High-end PA system IP66 wall-mounted speaker
- Rated output power 20W/40W/50W
- With power tap for 70V/100V and 8Ω
- 1×5", 1×6.5" or 1×8" for woofer and 1×1" for tweeter
- Exclusive optimal bass enhancement technology
- Quick installation with water-proof brackets
- Fashionable appearance with extraordinary sound quality

### Specification:

Model	WP-S01	WP-S02	WP-S03
Tweeter	1"(25 mm) Silk soft dome	1"(25mm) Silk soft dome	1.1"(28mm) Silk soft dome/Aluminum dome
Woofer	5"(125mm) Graphite Cone, Rubber Surround	6.5"(165mm) Graphite Cone, Rubber Surround	8"(203mm) Graphite Cone, Rubber Surround
Frequency Range	100Hz-20kHz(+/-3dB)	90Hz-20kHz(+/-3dB)	80Hz-20kHz(+/-3dB)
Power RMS	40W program, 20W	80W program, 40W	80W program, 50W
Sensitivity	85dB	86dB	87dB
Taps	8Ω, 0, 20W, 10W, 5W, 2.5W	8Ω, 0, 40W, 20W, 10W, 5W	8Ω, 0, 50W, 25W, 12.5W, 6.25W
Impedance	8 Ω	8 Ω	8 Ω
Termination	Plugged Terminal Blocks	Plugged Terminal Blocks	Plugged Terminal Blocks
Attachment	Brackets, Grille	Brackets, Grille	Brackets, Grille
Dimensions HWD	258mm x 170mm x 168mm	285mm x 198mm x 195mm	381mm x 250mm x 250mm
Certifications	IP66	IP66	IP66
Material	ABS	ABS	ABS

Ideal for small, medium, and large spaces, such as shopping malls, supermarkets, exhibition centers, and auditoriums, School gymnasiums, playgrounds, and campus-wide PA systems, Outdoor squares, parks, scenic areas, and large parking lots. Etc.,