

WS-620/WS-630/WS-640 20W/30W/40W IP66 Wall Mount Speaker



Features:

- IP66, all weather speaker for indoor and outdoor use
- With power tap for 70V/100V and 8Ω
- Rated output power 20W/40W
- 1×5", 1×6.5" or 1×8" for woofer and 1×1" for tweeter
- Quick installation with water-proof brackets
- Fashionable appearance with extraordinary sound quality

Specification:

Model	WS-620	WS-630	WS-640
Tweeter	1" (25 mm) Silk soft dome	1" (25 mm) Silk soft dome	1.1" (28 mm) Silk soft dome
Woofer	4" (100 mm) Graphite Cone, Rubber Surround	5" (125 mm) Graphite Cone, Rubber Surround	6.5" (165 mm) Graphite Cone, Rubber Surround
Frequency Range (±3dB)	70 Hz – 20 kHz	65 Hz – 20 kHz	52 Hz – 20 kHz
Power Handling (RMS)	40W Program, 20W (IEEE 219)	60W Program, 30W (IEEE 219)	60W Program, 40W (IEEE 219)
Sensitivity	83 dB	85 dB	87 dB
Power Taps	8Ω, 0, 20W, 10W, 5W, 2.5W	8Ω, 0, 30W, 15W, 7.5W, 3.75W	8Ω, 0, 40W, 20W, 10W, 5W
Impedance	8 Ω (common for all models)		
Termination	Standard rotary connector (common for all models)		
Included Accessories	Brackets, Waterproof cover, Grille (common for all models)		
Dimensions (H×W×D)	235.5 × 146.5 × 140.5 mm	269 × 168 × 165.5 mm	309 × 196 × 183 mm
Certifications	IP66 (common for all models)		
Cabinet Material	PP (Polypropylene) (common for all models)		