

## WS-6020/WS-6030/WS-6040

### 20W/30W/40W Wall Mount Speaker with Power Tap



#### Features:

- Input 70V/100V/8Ω
- Wide Freq.Resp.: 95Hz-20KHz
- Max SPL: 103±2dB
- High sensitivity: 90±2dB
- Wall mount type loudspeaker
- Metal grille and ABS enclosure of black color
- Equipped with hanging holes for mounting convenient

#### Specification:

Model	WS-6020	WS-6030	WS-6040
Speaker Unit	4" × 1, 1" × 1	5" × 1, 1" × 1	6.5" × 1, 1" × 1
Sensitivity (1m, 1W)	90 ± 2 dB	90 ± 2 dB	91 ± 2 dB
MAX. SPL (1m)	103 ± 2 dB	105 ± 2 dB	107 ± 2 dB
Frequency Response	95 Hz – 20 kHz	80 Hz – 20 kHz	65 Hz – 20 kHz
Rated Power	20 W	30 W	40 W
Power Tap Options (70V)	20W, 15W, 8W, 4W, 2W	30W, 15W, 8W, 5W, 2.5W	40W, 20W, 10W, 5W, 2.5W
Power Tap Options (100V)	20W, 15W, 8W, 4W	30W, 15W, 8W, 5W	40W, 20W, 10W, 5W
Power Tap Option (8Ω)	20 W	30 W	40 W
Constant Voltage Support	70V / 100V (common)		
Constant Resistance Support	8Ω (common)		
Dimensions (H × W × D)	255 × 176 × 170 mm	280 × 194 × 185 mm	310 × 215 × 203 mm
Net Weight	2.6 kg	3.2 kg	4.6 kg